

OS1 9/125 micron Singlemode Patchcordlar

Core iç çapı: 9micron
Core dis çapı: 125micron

Kayıp değeri: max. 0.20 dB (MTRJ max. 0.50 dB)
Geri yansima kaybı: UPC > 50dB , APC > 60dB

Kablo dis çapı: 2mm / 2.2mm / 2.8mm / 3mm
Bükülme çapı: 30 mm
Metraj: 1m - 10m (+/- 10mm)
Diğer metrajlar isteğe göre yapılır

Ayırma uzunluğu (Duplex): 150mm (+/- 10mm)
Zayıflama (dB/km): (1310/1550) 0.38 / 0.24
Dis kilif rengi: Sarı

Güç elemanları: Aramid kevlar ip
Dis kilif materyali: LSZH
Isteğe göre PVC yapılabilir
Atese dayanıklılık: IEC 60332-01
Kurulum sıcaklığı: (-40) - (+50)
Uygunluk: IEC 874-14

OS1 9/125 micron Singlemode Patchcords

Core ID: 9micron
Core OD: 125micron

Insertion loss max. 0.20 dB (MTRJ max. 0.50 dB)
Return loss: UPC > 50dB , APC > 60dB

Jacket OD: 2mm / 2.2mm / 2.8mm / 3mm
Bending radius: 30 mm
Length: 1m - 10m (+/- 10mm)
Other lengths available upon request

Split length (Duplex): 150mm (+/- 10mm)
Attenuation (dB/km): (1310/1550) 0.38 / 0.24
Jacket colour: Yellow

Strength member: Aramid yarn
Jacket material: LSZH
PVC available upon request
Flame resistance: IEC 60332-01
Operating Temperature (Celsius): (-40) - (+50)
Intermateability: IEC 874-14



ST-ST-OS1-D-Y-1



LC-LC-OS1-D-Y-2



SC-LC-OM1-D-O-2

